OVERVIEW



1. Power connector	5. Headphone / microphone combo jack (3.5mm)
2. USB 3.2 Gen 1	6. Card reader
3. HDMI	7. USB 3.2 Gen 1
4. USB-C 3.2 Gen 1	

IdeaPad Slim 3 16IRU8

PERFORMANCE

Processor

Processor Family

Intel® U-series or 13th Generation Intel® Core™ i3 / i5 / i7 Processor

Processor**

Processor Name	Cores	Threads	Base Frequency	Max Frequency	Cache	Processor Graphics
U300	5 (1 P-core + 4 E- core)	6	P-core 1.2GHz / E-core 0.9GHz	P-core 4.4GHz / E-core 3.3GHz	8MB	Intel® UHD Graphics
Core i3-1315U	6 (2 P-core + 4 E- core)	8	P-core 1.2GHz / E-core 0.9GHz	P-core 4.5GHz / E-core 3.3GHz	10MB	Intel® UHD Graphics
Core i5-1335U	10 (2 P-core + 8 E-core)	12	P-core 1.3GHz / E-core 0.9GHz	P-core 4.6GHz / E-core 3.4GHz	12MB	Intel [®] Iris [®] Xe Graphics ^[1]
Core i7-1355U	10 (2 P-core + 8 E-core)	12	P-core 1.7GHz / E-core 1.2GHz	P-core 5.0GHz / E-core 3.7GHz	12MB	Intel® Iris® Xe Graphics ^[2]

Notes:

[1], [2] Intel[®] Iris[®] Xe Graphics capability requires system to be configured with dual-channel memory. On the system with single-channel memory, Intel[®] Iris[®] Xe Graphics will function as Intel[®] UHD Graphics.

Operating System

Operating System**

- Windows® 11 Pro
- Windows® 11 Home
- Windows[®] 11 Home Single Language
- Windows® 11 Home Single Language in S mode
- Windows[®] 11 Home in S mode
- No preload operating system

Graphics

Graphics**

Graph	ics	Туре	Memory	TGP	Key Features
Intel [®] UHD Gr	aphics	Integrated	Shared	Share CPU TDP	DirectX® 12.1
Intel [®] Iris [®] Xe	Graphics ^[1]	Integrated	Shared	Share CPU TDP	DirectX® 12.1

Notes:

[1] Intel® Iris® Xe Graphics capability requires system to be configured with dual-channel memory. On the system with single-channel memory, Intel® Iris® Xe Graphics will function as Intel® UHD Graphics.

Monitor Support

Monitor Support

Supports up to 3 independent displays (native display and 2 external monitors via HDMI® and USB-C®)

- HDMI® supports up to 4K@30Hz
- USB-C[®] supports up to 4K@60Hz

Chipset

Chipset

Intel[®] SoC (System on Chip) platform

Memory

Max Memory

- 4GB soldered memory, not upgradable
- 8GB soldered memory, not upgradable
- 16GB soldered memory, not upgradable

Memory Slots**

- Memory soldered to systemboard, no slots, single-channel (4GB or 8GB models)
- Memory soldered to systemboard, no slots, dual-channel (16GB models)

Memory Type

LPDDR5-4800

Storage

Storage Support^[1]

- 128GB UFS 3.1 on systemboard
- One drive, up to 1TB M.2 2242 SSD

Storage Slot

- UFS on systemboard, no slots (UFS models)
- One M.2 PCIe[®] 4.0 x4 slot (M.2 SSD models)

Storage Type

Disk Type	Interface	Offering
Flash Memory	UFS 3.1 ^[2]	128GB
M.2 2242 SSD	PCIe® NVMe®, PCIe® 3.0 x4	128GB
M.2 2242 SSD	PCIe® NVMe®, PCIe® 4.0 x4	256GB / 512GB / 1TB

Notes:

[1] The storage capacity supported is based on the test results with current Lenovo[®] storage offerings.[2] UFS 3.1 storage is downgraded to closer to UFS 2.1 due to platform limitations.

Removable Storage

Card Reader

SD card reader

Multi-Media

Audio Chip

High Definition (HD) Audio

Speakers

User-facing stereo speakers, 1.5W x2, optimized with Dolby Audio™

Microphone

Dual-microphone array

Camera**

- FHD 1080p, with privacy shutter, fixed focus
- HD 720p, with privacy shutter, fixed focus

Battery

Battery

Integrated Li-Polymer 47Wh battery, supports Rapid Charge (charge up to 80% in 1hr)

Max Battery Life^[1]

MobileMark® 2018@200nits: 8.1 hr Local video (1080p) playback@150nits: 12 hr

Notes:

[1] All battery life claims are approximate maximum and based on results using the MobileMark® 2014, MobileMark® 2018, MobileMark® 25, MobileMark® 30, JEITA 2.0, JEITA 3.0, continuous 1080p video playback (with 150nits brightness and default volume level) or Google Power Load Test (PLT) battery-life benchmark tests. Actual battery life will vary depending on many factors such as product configuration and usage, software use, wireless functionality, power management settings, and screen brightness. The maximum capacity of the battery will decrease with time and use.

Power Adapter

Power Adapter

IdeaPad Slim 3 16IRU8

Lenovo

65W round tip (3-pin) AC adapter, 100-240V, 50-60Hz

DESIGN

Display

Display

Size	Resolution	Touch	Туре	Brightness	Surface	Aspect Ratio	Contrast Ratio	Color Gamut	Viewing Angle (L/R/U/D)
16″	WUXGA (1920x1200)	None	IPS ^[1]	300nits	Anti- glare	16:10	1000:1	45% NTSC	85° / 85° / 85° / 85°

Touchscreen

Non-touch

Notes:

[1] IPS (in-plane switching) technology may refer to IPS, PLS, ADS, AHVA, AAS.

Input Device

Keyboard

6-row, multimedia Fn keys, numeric keypad

Keyboard Backlight

- LED backlight
- Non-backlight

Touchpad

Buttonless Mylar® surface multi-touch touchpad, supports Precision TouchPad (PTP), 75 x 120 mm (2.95 x 4.72 inches)

Mechanical

Dimensions (WxDxH)^[1]

359.2 x 257 x 17.9 mm (14.14 x 10.12 x 0.70 inches)

Weight^[2]

Starting at 1.74 kg (3.84 lbs)

Case Color**

- Abyss blue
- Arctic grey

Surface Treatment

Painting

Case Material

PC-ABS (top), PC-ABS (bottom)

Notes:

[1] The system dimensions may vary depending on configurations.

[2] The system weight is approximate and based on results in Lenovo[®] lab, which varies depending on the source of component, variance of the distribution of each component, and manufacturing process. It may not be the exact weight for each specific model.

CONNECTIVITY

Network

Ethernet

No onboard Ethernet

WLAN + Bluetooth®**

- Wi-Fi[®] 5, 802.11ac 2x2 Wi-Fi[®] + Bluetooth[®] 5.1, M.2 Card
- Wi-Fi[®] 6, 802.11ax 2x2 Wi-Fi[®] + Bluetooth[®] 5.2, M.2 card^[1]

Notes:

[1] Wi-Fi® 6 full features might be limited by country-level restrictions.

Ports^{III}

Standard Ports

- 2x USB 3.2 Gen 1
- 1x USB-C[®] 3.2 Gen 1 (support data transfer, Power Delivery and DisplayPort[™] 1.2)
- 1x HDMI® 1.4
- 1x Headphone / microphone combo jack (3.5mm)
- 1x Card reader
- 1x Power connector

Notes:

[1] The transfer speed of following ports will vary and, depending on many factors, such as the processing speed of the host device, file attributes and other factors related to system configuration and your operating environment, will be slower than theoretical speed.

USB 2.0: 480 Mbit/s;

USB 3.2 Gen 1 (SuperSpeed USB 5Gbps, formerly USB 3.0 / USB 3.1 Gen 1): 5 Gbit/s;

USB 3.2 Gen 2 (SuperSpeed USB 10Gbps, formerly USB 3.1 Gen 2): 10 Gbit/s; USB4[®] 20Gbps / USB 3.2 Gen 2x2 (SuperSpeed USB 20Gbps): 20 Gbit/s;

USB4[®] 40Gbps (USB 40Gbps): 40 Gbit/s;

Thunderbolt[™] 3/4: 40 Gbit/s.

Docking

Docking

Various docking solutions supported via USB-C[®]. For more compatible docking solutions, please visit <u>Docking for IdeaPad[®] Slim 3 16IRU8</u>

SECURITY & PRIVACY

Security

Security Chip

Firmware TPM 2.0 integrated in SoC

Fingerprint Reader

- Touch style fingerprint reader integrated in power button
- No fingerprint reader

BIOS Security

- Administrator password
- Power-on password
- Hard disk password (M.2 SSD models only)
- Self-healing BIOS

Other Security

Camera privacy shutter

SERVICE

Warranty

Base Warranty**

- 1-year courier or carry-in service
- 1-year courier or carry-in with 2-year system board service (Korea only)
- 2-year (1-yr battery) courier or carry-in service
- 3-year (1-yr battery) courier or carry-in service

ACCESSORIES

Bundled Accessories

Bundled Accessories

None

OPERATING REQUIREMENTS

Operating Environment

Temperature^[1]

- At altitudes up to 2438 m (8,000 ft)
 - Operating: 5°C to 35°C (41°F to 95°F)
- Storage: 5°C to 43°C (41°F to 109°F)
- At altitudes above 2438 m (8,000 ft)
- Maximum temperature when operating under the unpressurized condition: 31.3°C (88°F)

Relative Humidity

- Operating: 8% to 95% at wet-bulb temperature 23°C (73°F)
- Storage: 5% to 95% at wet-bulb temperature 27°C (81°F)

Altitude

Maximum altitude (without pressurization): 3048 m (10,000 ft)

Notes:

[1] When you charge the battery, its temperature must be no lower than 10°C (50°F).

CERTIFICATIONS

Green Certifications^{ID}

Green Certifications^[2]

- ENERGY STAR[®] 8.0
- EPEAT[™] Silver Registered^[3]
- ErP Lot 6/26
- RoHS compliant

Notes:

[1] The items listed under the "Green Certifications" section may not only refer to certification but also registration or self-declaration. For ESG & regulatory compliance documents, please visit <u>https://compliance.lenovo.com</u>.

[2] EPEAT[™] registration and ENERGY STAR[®] certification are optional and only available on the models with preloaded OS. Please visit <u>epeat.net</u> and <u>energystar.gov</u> for more information.

[3] EPEAT[™] is registered where applicable, please visit <u>epeat.net</u> for registration status by country.

Other Certifications

Mil-Spec Test

MIL-STD-810H military test passed (21 test items)

Other Certifications

TÜV Rheinland[®] Low Blue Light (Software Solution)

- Feature with ** means that only one offering listed under the feature is configured on selected models.
- Lenovo reserves the right to change specifications or other product information without notice. Lenovo is not responsible for photographic or typographical errors. LENOVO PROVIDES THIS PUBLICATION "AS IS," WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some jurisdictions do not allow disclaimer of express or implied warranties in certain transactions, therefore this disclaimer may not apply to you.
- The specifications on this page may not be available in all regions, and may be changed or updated without notice.

PSREF Lenovo Porci Product Specifications Reference











